

Light Commercial & Residential MULTI SPLIT

- 120 Multi Split Overview
- 122 Outdoor Units Lineup
- 124 2 – 8 Rooms Connectable Indoor Units
- 126 Simultaneous Multi Connectable Indoor Units
- 168 Feature Explanation & Summary



Refrigerant type R32 models

2 Rooms Multi

128 **New** 2 Rooms Multi

Simultaneous Multi

136 **New** Simultaneous Multi Twin/Triple

2 Rooms Multi Split Indoor Units

142 **New** 2 Rooms Multi Indoor Units Specifications

146 **New** 2 Rooms Multi Combination Table



Refrigerant type R410A models

2 – 8 Rooms Multi

130 2 & 3-4 Rooms Multi

132 5-6 Rooms Multi

134 8 Rooms Multi

Simultaneous Multi

138 Simultaneous Multi Twin/Triple

140 Simultaneous Multi Twin/Triple/Double Twin


2 – 8 Rooms Multi Split Indoor Units

144 2-8 Rooms Indoor Units Specifications

147 2-8 Rooms Multi Combination Table

Control several indoor units with one outdoor unit. Build the system you desire.

If you want to keep a large floor as well as many rooms comfortable, we recommend to use our Multi Splits to build a compact system using just one outdoor unit. Choose from a large lineup of indoor units, which match up well to your rooms. You can mix and match them as you like. Build the system that is just right for you.



Multi Split Overview

Space-saving multi outdoor units can connect up to 8 indoor units in multiple rooms. New refrigerant R32 models are additionally added. Multi split type can be introduced in various situations like in homes, in offices and stores to provide environment-friendly comfort.



NEW

2 Rooms Multi



14 class

18 class

2-8 Rooms Multi

2-8 Rooms Multi type units are recommended for situations that require air conditioning in multiple rooms such as in family house or offices. Between 2 to 8 indoor units can be connected and individually operated. A variation of individual and central remote controller are available for operation control, time scheduling of each room and energy savings. Due to space - saving outdoor unit enables installation on balcony or under a waist-high window.



2 & 3-4 Rooms Multi



2 Rooms 14/18 class

5-6 Rooms Multi



36/45 class



3 Rooms 18/24 class

8 Rooms Multi



45 class



4 Rooms 30 class



NEW

Twin/Triple



Twin 36 class
(Single phase)



Twin/Triple 45/54 class
(Single phase)



Twin/Triple



36/45/54 class
(Single phase/3 phase)

Twin/Triple/ Double Twin



























72/90 class
(3 phase)

Simultaneous Multi

Simultaneous Multi type is recommended for situations where multiple indoor units need to be operated simultaneously such as for a small building, for small office building entrance, meeting room, educational facility hall, and other large spaces. Up to 4 indoor units can be operated simultaneously. This type is suitable for office spaces with large areas and properties with unusual floor layout.

MULTI SPLIT

Outdoor Units Lineup

				Class	14	18
				Cooling rated capacity (kW)	4	5
2 & 3-4 Rooms Multi	2 Rooms Multi Up to 2 units				AOYG14KBTA2	AOYG18KBTA2
					AOYG14LAC2	AOYG18LAC2
	3 Rooms Multi Up to 3 units					
	4 Rooms Multi Up to 4 units					
5-6 Rooms Multi	5 Rooms Multi Up to 5 units					
	6 Rooms Multi Up to 6 units					
8 Rooms Multi Up to 8 units						
Simultaneous Multi	Twin Single phase					
	Twin/Triple Single phase					
	Twin/Triple Single phase					
	Twin/Triple 3 phase					
	Twin/Triple/Double Twin 3 phase					

Note: **1. 2 Rooms Multi:** Connectable indoor units are 2 units.
 AOYG14KBTA2: Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.
 AOYG18KBTA2: Total capacity of indoor units connected must be between 4.0 kW and 7.5 kW.
 AOYG14LAC2: Total capacity of indoor units connected must be between 4.0 kW and 6.0 kW.
 AOYG18LAC2: Total capacity of indoor units connected must be between 4.0 kW and 7.0 kW.

2. 3 Rooms Multi: Connectable indoor units are 2 to 3 units.
 AOYG18LAT3: Total capacity of indoor units connected must be between 4.0 kW and 8.5 kW.
 AOYG24LAT3: Total capacity of indoor units connected must be between 4.0 kW and 10.5 kW.
3. 4 Rooms Multi: Connectable indoor units are 3 to 4 units.
 AOYG30LAT4: Total capacity of indoor units connected must be between 7.5 kW and 14.0 kW.

18 5.4	24 6.8	30 8	36 10	45		54 14	72 19	90 22
AOYG18LAT3*	AOYG24LAT3*							
		AOYG30LAT4*						
			AOYG36LBLA5*					
				AOYG45LBLA6*				
					AOYG45LBT8*			
			AOYG36KBTB	AOYG45KBTB				
						AOYG54KBTB		
			AOYG36LBTB	AOYG45LBTB*1		AOYG54LBTB*2		
			AOYG36LATT	AOYG45LATT		AOYG54LATT		
							AOYG72LRLA	AOYG90LRLA

4. 5 Rooms Multi: Connectable indoor units are 2 to 5 units

AOYG36LBLA5: Total capacity of indoor units connected must be between 7.5 kW and 15.5 kW.

5. 6 Rooms Multi: Connectable indoor units are 2 to 6 units

AOYG45LBLA6: Total capacity of indoor units connected must be between 9.5 kW and 18.0 kW.

6. 8 Rooms Multi: Connectable indoor units are 2 to 8 units

AOYG45LBT8: Total capacity of indoor units connected must be between 11.0 kW and 18.0 kW.





FUJITSU GENERAL (Euro) GmbH participates in the ECP programme for AIR CONDITIONERS. Check ongoing validity of certificate: www.eurovent-certification.com
* Models so marked are not ECC certified.

MULTI SPLIT

2 – 8 Rooms Connectable Indoor Units



Type		2 Rooms	
Model name		AOYG14KBTA2	AOYG18KBTA2
Multi Split Outdoor Unit			
Capacity (kW)	Cooling	4.0	5.0
	Heating	4.4	5.6

Indoor Unit	BTU	kW Class	AOYG14KBTA2	AOYG18KBTA2
 ASYG07/09/12/14KGTB	7,000	2.0	●	●
	9,000	2.5	●	●
	12,000	3.5	●	●
	14,000	4.0	–	●
 AUXG07/09/12/14KVLA	7,000	2.0	●	●
	9,000	2.5	●	●
	12,000	3.5	●	●
	14,000	4.0	–	●
 ARXG07/09/12/14KSLAP	7,000	2.0	●	●
	9,000	2.5	●	●
	12,000	3.5	●	●
	14,000	4.0	–	●
 ARXG07/09/12/14KLLAP	7,000	2.0	●	●
	9,000	2.5	●	●
	12,000	3.5	●	●
	14,000	4.0	–	●





Type	2 Rooms		3 Rooms		4 Rooms	5 Rooms	6 Rooms	8 Rooms	
Model name	AOYG 14LAC2	AOYG 18LAC2	AOYG 18LAT3	AOY G24LAT3	AOYG30LAT4	AOYG36LBA5	AOYG45LBA6	AOYG45LBT8	
Multi Split Outdoor Unit									
Capacity (kW)	Cooling	4.0	5.0	5.4	6.8	8.0	10.0	12.5	14.0
	Heating	4.4	5.6	6.8	8.0	9.6	12.0	13.5	16.0

Indoor Unit	BTU	kW Class								
	7,000	2.0	●	●	●	●	●	●	●	●
	9,000	2.5	●	●	●	●	●	●	●	●
	12,000	3.5	●	●	●	●	●	●	●	●
	14,000	4.0	—	●	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
	24,000	7.0	—	—	—	—	●	—	●	●
	9,000	2.5	—	●	●	●	●	●	●	●
	12,000	3.5	—	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	7,000	2.0	—	●	●	●	●	●	●	●
	9,000	2.5	—	●	●	●	●	●	●	●
	12,000	3.5	—	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
	18,000	5.0	—	—	—	●	●	●	●	●
	7,000	2.0	—	●	●	●	●	●	●	—
	9,000	2.5	—	●	●	●	●	●	●	—
	12,000	3.5	—	●	●	●	●	●	●	—
	14,000	4.0	—	—	●	●	●	●	●	—
	18,000	5.0	—	—	—	●	●	●	●	—
	7,000	2.0	—	●	●	●	●	●	●	●
	9,000	2.5	—	●	●	●	●	●	●	●
	12,000	3.5	—	●	●	●	●	●	●	●
	14,000	4.0	—	—	●	●	●	●	●	●
18,000	5.0	—	—	—	●	●	●	●	●	

MULTI SPLIT

Simultaneous Multi Connectable Indoor Units



Type	4HP	5HP	6HP		
Model name	AOYG36KBTB	AOYG45KBTB	AOYG54KBTB		
Simultaneous Multi Outdoor Unit					
Capacity (kW)	Cooling	9.5	12.1	13.4	13.4
	Heating	10.8	13.5	15.5	15.5

Indoor Unit	BTU	kW Class	Twin			Triple
 AUXG18/22/24KVLA	18,000	5.0	● ×2	—	—	● ×3
	22,000	6.5	—	● ×2	—	—
	24,000	7.0	—	—	● ×2	—
 ARXG18KLLAP	18,000	5.0	● ×2	—	—	● ×3
	22,000	6.5	—	● ×2	—	—
 ARXG22/24KMLA	24,000	7.0	—	—	● ×2	—
	Separation tube			UTP-SX236A (18/22/24)		



Type	4HP		5HP		6HP		8HP	10HP
Model name	AOYG36LBTB	AOYG36LATT	AOYG45LBTB	AOYG45LATT	AOYG54LBTB	AOYG54LATT	AOYG72LRLA	AOYG90LRLA
Simultaneous Multi Outdoor Unit								
Capacity (kW)	Cooling	10.0	12.1	12.5	13.3	14.0	19.0	22.0
	Heating	11.2	14.0	14.0	15.0	16.0	22.4	27.0

Indoor Unit	BTU	kW Class	Twin		Triple	Twin	Triple	Double Twin	Twin	Triple	Double Twin
			● ×2	● ×2	● ×3	● ×2	● ×3	● ×4	● ×2	● ×3	● ×4
	18,000	5.0	● ×2	-	-	● ×3	-	-	● ×4	-	-
	22,000	6.5	-	● ×2	-	-	-	-	-	-	● ×4
	24,000	7.0	-	-	● ×2	-	-	● ×3	-	-	-
	30,000	8.8	-	-	-	-	-	-	-	● ×3	-
	36,000	10.6	-	-	-	● ×2	-	-	-	-	-
	45,000	12.5	-	-	-	-	-	-	● ×2	-	-
	18,000	5.0	● ×2	-	-	● ×3	-	-	● ×4	-	-
	22,000	6.5	-	● ×2	-	-	-	-	-	-	● ×4
	24,000	7.0	-	-	● ×2	-	-	● ×3	-	-	-
	30,000	8.8	-	-	-	-	-	-	-	● ×3	-
	36,000	10.6	-	-	-	-	● ×2	-	-	-	-
	45,000	12.5	-	-	-	-	-	-	-	● ×2	-
	18,000	5.0	● ×2	-	-	● ×3	-	-	● ×4	-	-
	22,000	6.5	-	● ×2	-	-	-	-	-	-	● ×4
	24,000	7.0	-	-	● ×2	-	-	● ×3	-	-	-
	30,000	8.8	-	-	-	-	-	-	-	● ×3	-
	36,000	10.6	-	-	-	-	● ×2	-	-	-	-
	45,000	12.5	-	-	-	-	-	-	-	● ×2	-
Separation tube			UTP-SX236A ×1	UTP-SX254A ×1	UTP-SX254 ×1	UTP-SX354A ×1	UTP-SX272A ×1	UTP-SX372A ×1	UTP-SX272A ×1	UTP-SX372A ×1	UTP-SX272A ×1, UTP-SX236A ×2

MULTI SPLIT




High energy saving

DC technology is used for compressor, indoor / outdoor fan motor and inverter controlling.



SEER 8.7^{*1} SCOP 4.7

*1: 14 model



Wide range of indoor units with various models

4 types / 16 models are lined up in the capacity range from 2.0 kW to 4.0 kW class. Wide range of requirements can be realized from in private homes, large shops and hotels.




Models equipped with the New R32 Refrigerant

Wall mounted type with sophisticated design



Middle and small capacity models are available. This makes it easier to install at small spaces.



Mini Duct



Compact Cassette



Slim Duct



14

18

Specifications


Model No.			AOYG14KBTA2	AOYG18KBTA2
Power Source			Single-phase, ~230V, 50Hz	
Rated Capacity (min-max)	Cooling	kW	4.0 (1.4-4.6)	5.0 (1.7-5.8)
	Heating		4.4 (1.1-5.5)	5.6 (1.8-7.0)
EER	Cooling	W/W	4.12	4.03
	Heating		4.63	4.59
Sound Pressure Level (High)	Cooling	dB(A)	47	47
	Heating		49	50
Sound Power Level (High)	Cooling		60	60
	Heating		62	62
Airflow Rate	Cooling/Heating	m ³ /h	1,670/1,670	1,960/2,020
Net Dimensions H × W × D			mm	632×799×290
Weight			kg(lbs)	33 (73)
Connection Pipe Diameter	Liquid	mm	6.35×2	6.35×2
	Gas		9.53 × 2	9.53 × 2
Max. Pipe Length	Total / Each		30 / 20	30 / 20
	Max. Height Difference	Between Outdoor Unit and Each Indoor Units.	m	15
Between Indoor Units.		10		10
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R32 (675)	R32 (675)
	Charge	kg(CO ₂ eq-T)	0.9 (0.574)	1.02 (0.689)

MULTI SPLIT


Dimensions

(Unit : mm)

AOYG14KBTA2



AOYG18KBTA2




MULTI SPLIT

2 & 3-4 Rooms Multi




Wide range of indoor units with various models

4 types / 16 models are lined up in the capacity range from 2.0 kW to 4.0 kW class. Wide range of requirements can be realized from in private homes, large shops and hotels.



Space-saving installation

Multiple indoor units can be connected to 1 outdoor unit, and long piping connection is also possible. Compared with single type, the outdoor unit can be installed in various places to realize the space-saving installation.




Flexible installation

Up to max. piping length of 70 m (AOYG30LAT4), max. height difference of 15 m can be supported. Multi type can be installed in large-size residence or buildings with multiple floors.



Max. Piping Length (Each Unit):
 20 m: AOYG14LAC2/18LAC2,
 25 m: AOYG18LAT3/24LAT3/30LAT4



Max. Height:
 15 m: AOYG14LAC2/18LAC2/18LAT3/
 24LAT3/30LAT4

Total Piping Length:
 30 m: AOYG14LAC2/18LAC2,
 50 m: AOYG18LAT3/24LAT3,
 70 m: AOYG30LAT4

2 Rooms: AOYG14LAC2 / AOYG18LAC2
 3 Rooms: AOYG18LAT3 / AOYG24LAT3
 4 Rooms: AOYG30LAT4



Specifications (2 Rooms, 3 Rooms, 4 Rooms)


Model No.			AOYG14LAC2	AOYG18LAC2	AOYG18LAT3	AOYG24LAT3	AOYG30LAT4
Power Source			Single-phase, ~230V, 50Hz				
Rated Capacity (min-max)	Cooling	kW	4.0 (1.4-4.4)	5.0 (1.7-5.6)	5.4 (1.8-6.8)	6.8 (1.8-8.5)	8.0 (3.5-10.1)
	Heating		4.4 (1.1-5.4)	5.6 (1.8-6.1)	6.8 (2.0-8.0)	8.0 (2.0-9.2)	9.6 (3.7-12.0)
EER	Cooling	W/W	3.67	3.21	4.00	3.51	3.60
	Heating		4.27	3.97	4.20	4.00	4.00
COP	Cooling	dB(A)	47	50	46	48	50
	Heating		49	51	47	49	51
Sound Pressure Level (High)	Cooling	dB(A)	61	63	65	68	68
	Heating		63	64	67	70	70
Airflow Rate	Cooling/Heating	m ³ /h	1,850/1,850	2,050/2,050	3,050/2,750	3,300/3,300	3,500/3,300
Net Dimensions H × W × D		mm	540×790×290	540×790×290	700×900×330	700×900×330	830×900×330
Weight		kg(lbs)	37 (82)	38 (84)	55 (121)	55 (121)	68 (150)
Connection Pipe Diameter	Liquid	mm	6.35×2	6.35×2	6.35×3	6.35×3	6.35×4 (*6.35×3, 9.52)
	Gas		9.52 × 2	9.52 × 2 *(9.52, 12.70)	9.52 × 2, 12.70 *(9.52 × 3)	9.52 × 2, 12.70 *(9.52 × 3)	9.52 × 2, 12.70 × 2 *(9.52 × 3, 12.70) *(9.52 × 2, 12.70, 15.88)
Max. Pipe Length	Total / Each	m	30 / 20	30 / 20	50 / 25	50 / 25	70 / 25
Max. Height Difference	Between Outdoor Unit and Each Indoor Units.		15	15	15	15	15
	Between Indoor Units.	10	10	10	10	10	
Operation Range	Cooling	°CDB	10 to 46	10 to 46	-10 to 46	-10 to 46	0 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-10 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	kg(CO2eq-T)	1.25 (2.6)	1.30 (2.7)	2.20 (4.6)	2.20 (4.6)	3.30 (6.9)

* Connect to connection valve by the adapter.


Dimensions

(Unit : mm)


**2 Rooms:
AOYG14LAC2/AOYG18LAC2**



**3 Rooms:
AOYG18LAT3/AOYG24LAT3**



**4 Rooms:
AOYG30LAT4**



MULTI SPLIT

5 – 6 Rooms Multi



Wide range of indoor units with various models

4 types / 16 models are lined up in the capacity range from 2.0 kW to 4.0 kW class. Wide range of requirements can be realized from in private homes, large shops and hotels.




Compact design

Multiple indoor units can be connected to 1 outdoor unit, and long piping connection is also possible. Compared with single type, the outdoor unit can be installed in various places to realize the space-saving installation.



Easy installation

All connected pipes and indoor units can be evacuated quickly via our centralized valve method. Requires evacuation only once




Central & Individual Control

- Batched control of up to 8 indoor units. The temperature, airflow volume, and remote control prohibition settings of all indoor units can be batched.
- Corresponds to 9 different languages (English, German, French, Spanish, Russian, Portuguese, Italian, Greek, and Turkish)
- Large backlight LED screen
- Large easy-to-see operation panel

Max. Controllable
1 multi system

Max. Controllable
8 indoor units



5 Rooms: AOYG36LBLA5
6 Rooms: AOYG45LBLA6




Specifications (5 Rooms, 6 Rooms)

Model No.			AOYG36LBLA5	AOYG45LBLA6
Power Source			Single-phase, ~230V, 50Hz	
Rated Capacity (min-max)	Cooling	kW	10.0 (3.5-12.5)	12.5 (3.5-14.0)
	Heating		12.0 (3.5-14.0)	13.5 (3.5-16.0)
EER	Cooling	W/W	4.10	3.50
COP	Heating		4.30	4.00
Sound Pressure Level (High)	Cooling	dB(A)	53	53
	Heating		55	55
Sound Power Level (High)	Cooling		67	67
	Heating		68	68
Airflow Rate	Cooling/Heating	m ³ /h	4,200/4,200	4,200/4,200
Net Dimensions H × W × D			998×970×370	998×970×370
Weight			94 (207)	94 (207)
Connection Pipe Diameter	Liquid	mm	6.35×5	6.35×6
	Gas		9.52 × 3, 12.70 × 2	9.52 × 4, 12.70 × 2
Max. Pipe Length			80 / 25	80 / 25
Max. Height Difference	Between Outdoor Unit and Each Indoor Units.	m	15	15
	Between Indoor Units.		10	10
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	kg(CO ₂ eq-T)	R410A (2,088)	R410A (2,088)
	Charge		4.00 (8.4)	4.00 (8.4)

Dimensions

(Unit : mm)




MULTI SPLIT




Compact outdoor unit

The compact design outdoor unit allows to be installed below a window and in a narrow space.



High seasonal efficiency

The actual performance is conducted under various outside temperatures depending on weather and seasons, furthermore, especially for multi system, not all the rooms are operated all the time. So over 90% of actual operation time, air conditioners are operated at partial capacity instead of rated capacity. Considering these, we focused on energy-saving performance which is based on actual use. Efficiency of part load performance was drastically improved by developing ALL DC and our own inverter system.



Innovated technology




High efficiency large fan:
High efficiency fan is mounted.



DC fan motor:
High performance and high efficiency has been realized by using a small DC fan motor.




Heat exchanger:
Reduced compact size and energy saving has been realized by utilizing high density piping design and 3-Row heat exchanger.



High efficiency DC twin rotary compressor:
A high performance, low noise, large capacity DC twin rotary compressor is used.


Quick comfort by optimized refrigerant control

Every room meets the set point most quickly and comfortably by optimized refrigerant control.



8 Rooms: AOYG45LBT8

Branch Box: UTP-PY03A / UTP-PY02A



Specifications (Outdoor unit/Branch box)

Outdoor Unit Model Name			AOYG45LBT8
Maximum Connectable Indoor Unit			8
Indoor Unit Connectable Capacity	Cooling	kW	11.0 - 17.5
Power source			Single-phase, ~230V, 50Hz
Rated Capacity	Cooling	kW	14.0
	Heating		16.0
Input Power	Cooling	kW	5.20
	Heating		5.07
Airflow rate	Cooling	m ³ /h	4,650
	Heating		4,800
Sound Pressure Level	Cooling	dB(A)	56
	Heating		58
Heat Exchanger Fin			Plate fin coil
Net Dimensions H × W × D			914×970×370
Weight			98 (217)
Connection Pipe Diameter (Liquid / Gas)			9.52/15.88
Max Pipe Length			115 (Total)
Max Height Difference (O.U ~ I.U)			30
Operating Range	Cooling	°CDB	-5 to 46
	Heating		-15 to 24
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	
	Charge	kg(CO ₂ eq-T)	3.45 (7.2)

Branch Box Model Name			UTP-PY03A	UTP-PY02A
Connectable Indoor Unit			1 to 3 Units	1 to 2 Units
Power source			Single-phase, ~230V, 50Hz	Single-phase, ~230V, 50Hz
Available Voltage Range			198-264V	198-264V
Power Consumption	W		10	10
Running Current	A		0.05	0.05
Net Dimensions H × W × D			195×433×370	195×433×370
Weight			9 (20)	9 (20)
Connection pipe diameter	Liquid	°CDB	Main: 9.52×1, Branch:6.35×3	Main: 9.52×1, Branch:6.35×2
	Gas		Main: 15.88×1, Branch:12.70×3	Main: 15.88×1, Branch:12.70×2
	Method		Flare	Flare


Note: Specifications are based on the following conditions.

- In case of connecting two indoor units(7 kW class).
- These are the measured values in the manufacturer's anechoic chamber.
- Cooling: Indoor temp. of 27°CDB/19°CWB, outdoor temp. of 35°CDB/24°CWB Heating: Indoor temp. of 20°CDB/15°CWB, outdoor temp. of 7°CDB/6°CWB
Pipe length: 5 m (Outdoor unit - Branch box), 3 m (Branch box - Indoor unit) Height difference : 0 m


Dimensions

(Unit: mm)


Outdoor Unit: AOYG45LBT8



Branch Box : UTP-PY03A (3 branches type)



Branch Box : UTP-PY02A (2 branches type)




MULTI SPLIT




Supports various installation scenes from office to commercial space, inside the same room and multi connection of up to 3 indoor units.

Selection of indoor units according to the room shape and heat load, like number of people and lighting conditions. Most comfortable air flow distribution can be realized.

Installation according to floor layout




Installation according to lighting conditions



Design flexibility


Slim & Compact design

This model is much more compact than a conventional outdoor unit. Significant reduced height of the product supports installations in narrow spaces.



Flexible installation

Up to max. piping length of 50 m, max. height difference of 30 m can be supported. Multi type can be installed in large-size residence or buildings with multiple floors.



New Indoor unit lineup

3 types 6 models indoor units are provided, so you can select them depending on your room size and conditions.



Compact Cassette



Slim Duct



Duct

Model: AOYG36KBTB / AOYG45KBTB / AOYG54KBTB



36



45/54

Specifications (Indoor units/Outdoor units)

Indoor Units Model No.				Compact Cassette		
				AUXG18KVLA	AUXG22KVLA	AUXG24KVLA
Power Source				Single-phase, ~230V, 50Hz		
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	680/580/490/410	830/740/600/450	930/830/600/450
	Heating	H/M/L/Q		800/680/580/450	860/760/700/530	930/850/700/530
Net Dimension H × W × D			mm	245x570x570	245x570x570	245x570x570
Weight			kg(lbs)	15 (33)	16 (35)	16 (35)
Cassette Grille				UTG-UFYF-W		

Indoor Units Model No.				Duct		
				ARXG18KLLAP	ARXG22KMLA	ARXG24KMLA
Power Source				Single-phase, ~230V, 50Hz		
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	940/880/820/750	1,100/910/750/580	1,100/910/750/580
	Heating	H/M/L/Q		940/880/820/750	1,100/910/750/580	1,100/910/750/580
Net Dimension H × W × D			mm	198x900x620	270x1,135x700	270x1,135x700
Weight			kg(lbs)	20 (44)	35 (77)	35 (77)


Outdoor Units Model No.			AOYG36KBTB	AOYG45KBTB	AOYG54KBTB
Capacity	Cooling	kW	9.5	12.1	13.4
	Heating		10.8	13.5	15.5
Power Source			Single-phase, ~230V, 50Hz		
Pdesign	Cooling	kW	—	—	—
	Heating (-10°C)		8.7	9.2	9.5
SEER	Cooling	W/W	6.10	—	—
SCOP	Heating		4.00	—	—
Annual Energy Consumption	Cooling	kWh/a	545	—	—
	Heating		3,043	—	—
Energy Efficiency Class	Cooling	—	A++	—	—
	Heating		A+	—	—
Sound Pressure Level (High)	Cooling	dB(A)	55	57	57
	Heating		55	57	59
Sound Power Level (High)	Cooling		70	71	73
	Heating		70	71	73
Airflow Rate	Cooling / Heating	m ³ /h	3,750/3,750	4,450/4,450	4,450/4,450
Net Dimension H × W × D			mm	788x940x320	998x940x320
Weight			kg(lbs)	52 (115)	67 (148)
Connection Pipe Diameter (Liquid / Gas)			mm	9.52/15.88	9.52/15.88
Max Pipe Length (Pre-Charge)			m	50 (30)	50 (30)
Height Difference			m	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)	kg(CO2eq-T)	R32 (675)	R32 (675)	R32 (675)
	Charge		1.90(1.283)	2.70(1.823)	2.70(1.823)
Separation tube			UTP-SX236A (Twin)		

• Different type and capacity indoor units cannot be connected.
• The above table is the value for connecting with cassette type.


Dimensions

(Unit : mm)

AOYG36KBTB



AOYG45KBTB / AOYG54KBTB




MULTI SPLIT




Supports various installation scenes from office to commercial space, inside the same room and multi connection of up to 3 indoor units.

Selection of indoor units according to the room shape and heat load, like number of people and lighting conditions. Most comfortable air flow distribution can be realized.


Installation according to floor layout



Installation according to lighting conditions




Installation according to layout and lighting conditions



Simultaneous control

Max 16 indoor units are simultaneously controlled with a wired remote controller.



Set the indoor unit number using DIP switch on indoor unit circuit board.

Indoor unit lineup

4 types 9 models indoor units are provided, so you can select them depending on your room size and conditions.



Compact Cassette



Slim Duct



Duct



Floor/Ceiling Universal

Model : AOYG36LBTB / AOYG45LBTB / AOYG54LBTB
 AOYG36LATT [3phase] / AOYG45LATT [3phase] / AOYG54LATT [3phase]



Specifications (Indoor units/Outdoor units)

Indoor Units Model No.				Compact Cassette		
				AUYG18VLB	AUYG22VLA	AUYG24VLA
Power Source				Single-phase, ~230V, 50Hz		
Airflow Rate	Cooling	H/M/L/Q	m³/h	750/610/520/410	930/830/600/450	930/830/600/450
	Heating	H/M/L/Q		800/710/600/450	930/860/700/530	930/830/600/450
Net Dimension H × W × D				mm		
Weight				kg(lbs)		
Cassette Grille				UTG-UFYD-W		


Indoor Units Model No.				Duct			Floor/Ceiling Universal		
				ARYG18LLTB	ARYG22LMLA	ARYG24LMLA	ABYG18LVTB	ABYG22LVTB	ABYG24LVTB
Power Source				Single-phase, ~230V, 50Hz			Single-phase, ~230V, 50Hz		
Airflow Rate	Cooling	H/M/L/Q	m³/h	940/880/820/750	1,100/910/750/580	780/700/560/500	980/820/680/540	980/820/680/540	
	Heating	H/M/L/Q		940/880/820/750	1,100/910/750/580	780/700/560/500	980/820/680/540	980/820/680/540	
Net Dimension H × W × D				mm			mm		
Weight				kg(lbs)			kg(lbs)		

Outdoor Units Model No.				AOYG36LBTB	AOYG45LBTB	AOYG54LBTB	AOYG36LATT	AOYG45LATT	AOYG54LATT
Capacity	Cooling	kW	10.0	12.1	13.3	10.0	12.5	14.0	
	Heating		11.2	14.0	15.0	11.2	14.0	16.0	
Power Source				Single-phase, ~230V, 50Hz			3-phase, ~400V, 50Hz		
Pdesign	Cooling	kW	10.0	-	-	10.0	-	-	
	Heating (-10°C)		10.0	-	-	10.0	-	-	
SEER	Cooling	W/W	5.56	-	-	6.00	-	-	
SCOP	Heating	W/W	3.90	-	-	4.00	-	-	
Annual Energy Consumption	Cooling	kWh/a	629	-	-	583	-	-	
	Heating		3,588	-	-	3,499	-	-	
Energy Efficiency Class	Cooling	A	-	-	A+	-	-		
	Heating	A	-	-	A+	-	-		
Sound Pressure Level (High)	Cooling	dB(A)	52	54	55	51	54	55	
Sound Power Level (High)	Heating		69	70	72	69	69	71	
Airflow Rate	Cooling / Heating	m³/h	6,200/6,200	6,750/6,200	6,850/6,750	6,200/6,200	6,750/6,200	6,900/6,900	
Net Dimension H × W × D				mm			mm		
Weight				kg(lbs)			kg(lbs)		
Connection Pipe Diameter (Liquid / Gas)				mm			mm		
Max Pipe Length (Pre-Charge)				m			m		
Height Difference				m			m		
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)		
	Charge	kg(CO2eq-T)	3.45 (7.2)	3.45 (7.2)	3.45 (7.2)	3.45 (7.2)	3.45 (7.2)	3.45 (7.2)	
Separation tube				UTP-SX236A(Twin)			UTP-SX254A(Twin) / UTP-SX354A(Triple)		

*Different type and capacity indoor units cannot be connected.
 *The above table is the value for connecting with cassette type.

Dimensions

(Unit : mm)




MULTI SPLIT




Support various applications from open plan offices to retail stores, with up to 4 indoor units.

Selection of indoor units according to the room shape and heat load, like number of people and lighting conditions. Most comfortable air flow distribution can be realized.


Installation according to floor layout




Installation according to lighting conditions



Installation according to layout and lighting conditions




Installation according to large space



Simultaneous control

Max 16 indoor units are simultaneously controlled with a wired remote controller.



Set the indoor unit number using DIP switch on indoor unit circuit board.

*When using a wireless remote controller, the following functions cannot be used: Timer operation, Sleep Timer operation, 10°C Heat operation

Indoor unit lineup

6 types 18 models indoor units are provided, so you can select them depending on your room size and conditions.



Compact Cassette



Cassette



Slim Duct



Duct



Floor/Ceiling Universal



Ceiling

Model: AOYG72LRLA [3phase] / AOYG90LRLA [3phase]



Specifications (Indoor units/Outdoor units)

Indoor Units Model No.				Compact Cassette, Cassette					
				AUYG18LVLB	AUYG22LVLA	AUYG24LVLA	AUYG30LRLE	AUYG36LRLE	AUYG45LRLA
Power Source				Single-phase, ~230V, 50Hz					
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	750/610/520/410	930/830/600/450	930/830/600/450	1,600/1,400/1,270/1,150	1,800/1,400/1,270/1,150	1,900/1,640/1,460/1,250
	Heating	H/M/L/Q		800/710/600/450	930/860/700/530	930/830/600/450	1,800/1,400/1,270/1,150	1,800/1,400/1,270/1,150	1,900/1,640/1,460/1,250
Net Dimension H × W × D			mm	245×570×570	245×570×570	245×570×570	288 × 840 × 840	288 × 840 × 840	288 × 840 × 840
Weight			kg(lbs)	15 (33)	16 (35)	16 (35)	26 (57)	26 (57)	26 (57)
Cassette Grille				UTG-UFYD-W			UTG-UGYA-W		

Indoor Units Model No.				Duct					
				ARYG18LLTB	ARYG22LMLA	ARYG24LMLA	ARYG30LMLE	ARYG36LMLE	ARYG45LMLA
Power Source				Single-phase, ~230V, 50Hz					
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	940/880/820/750	1,100/910/750/580	1,100/910/750/580	1,900/1,620/1,270/980	1,900/1,620/1,270/980	2,100/1,750/1,350/1,070
	Heating	H/M/L/Q		940/880/820/750	1,100/910/750/580	1,100/910/750/580	2,100/1,620/1,270/980	2,100/1,620/1,270/980	2,100/1,750/1,350/1,070
Net Dimension H × W × D			mm	198 × 900 × 620	270 × 1135 × 700	270 × 1135 × 700	270 × 1135 × 700	270 × 1135 × 700	270 × 1135 × 700
Weight			kg(lbs)	23 (51)	38 (84)	38 (84)	40 (88)	40 (88)	40 (88)

Indoor Units Model No.				Floor/Ceiling, Ceiling					
				ABYG18LVTB	ABYG22LVTA	ABYG24LVTA	ABYG30LRTE	ABYG36LRTE	ABYG45LRTE
Power Source				Single-phase, ~230V, 50Hz					
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	780/700/560/500	980/820/680/540	980/820/680/540	1,660/1,500/1,200/1,000	1,900/1,500/1,200/1,000	2,100/1,700/1,400/1,100
	Heating	H/M/L/Q		780/700/560/500	980/820/680/540	980/820/680/540	1,660/1,500/1,200/1,000	1,900/1,500/1,200/1,000	2,100/1,700/1,400/1,100
Net Dimension H × W × D			mm	199 × 990 × 655	199 × 990 × 655	199 × 990 × 655	240 × 1660 × 700	240 × 1660 × 700	240 × 1660 × 700
Weight			kg(lbs)	27 (60)	27 (60)	27 (60)	46 (101)	46 (101)	46 (101)


Outdoor Units Model No.			AOYG72LRLA		AOYG90LRLA	
Capacity	Cooling	kW	19.0		22.0	
	Heating		22.4		27.0	
Power Source			3-phase, ~400V, 50Hz			
Sound Pressure Level (High)	Cooling	dB(A)	55		55	
Airflow Rate	Cooling / Heating	m ³ /h	8,400/8,400		8,400/9,000	
Net Dimension H × W × D			mm		1,428×1,080×480	
Weight			kg(lbs)		163 (359)	
Connection Pipe Diameter (Liquid / Gas)			mm		12.7/25.4	
Max Pipe Length (Pre-Charge)			m		100 (30)	
Height Difference			m		30	
Operation Range	Cooling	°CDB	-15 to 46		-15 to 46	
	Heating		-20 to 24		-20 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)		R410A (2,088)	
	Charge	kg(CO ₂ eq-T)	5.6 (11.7)		7.1 (14.8)	

- Different type and capacity indoor units cannot be connected.
- The above table is the value for connecting with cassette type.

*: That specification is not fixed yet.


Dimensions

(Unit : mm)



MULTI SPLIT

New 2 Rooms Multi Indoor Units Specifications



Wall mounted



Model No.	Indoor unit			ASYG07KGTB	ASYG09KGTB	ASYG12KGTB	ASYG14KGTB
kW Class			kW	2.0	2.5	3.5	4.0
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating			41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	650/540/430/270	700/560/430/270	700/560/430/250	770/600/450/280
	Heating			720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions				270x834x215	270x834x215	270x834x215	270x834x215
Weight				10 (22)	10 (22)	10 (22)	10 (22)
Connection Pipe Diameter	Liquid/Gas			6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

Wall mounted



Model No.	Indoor unit			ASYG07KMTB	ASYG09KMTB	ASYG12KMTB	ASYG14KMTB
kW Class			kW	2.0	2.5	3.5	4.0
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating			41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	H	dB(A)	54	55	55	57
	Heating			56	57	58	59
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	650/540/430/270	700/560/430/270	700/560/430/270	770/600/450/280
	Heating			720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions				270x834x222	270x834x222	270x834x222	270x834x222
Weight				10 (22)	10 (22)	10 (22)	10 (22)
Connection Pipe Diameter	Liquid/Gas			6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52



Compact cassette Grid type



Model No.	Indoor unit			AUXG07KVLA	AUXG09KVLA	AUXG12KVLA	AUXG14KVLA
kW Class	kW			2.0	2.5	3.5	4.0
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/34/31/28	38/35/32/29
	Heating			34/32/29/27	34/32/29/27	37/34/31/29	43/38/34/30
Sound Power Level	Cooling	H	dB(A)	46	46	49	50
	Heating			47	47	49	55
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	790/680/580/450
Net Dimensions	mm			245x570x570	245x570x570	245x570x570	245x570x570
Weight	kg(lbs)			15 (33)	15 (33)	15 (33)	15 (33)
Panel				UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

Mini duct



Model No.	Indoor unit			ARXG07KSLAP	ARXG09KSLAP	ARXG12KSLAP	ARXG14KSLAP
kW Class	kW			2.0	2.5	3.5	4.0
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23
	Heating			29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23
Sound Power Level	Cooling	H	dB(A)	52	54	55	60
	Heating			53	56	57	62
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360
	Heating			550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360
Net Dimensions	mm			198x700x450	198x700x450	198x700x450	198x700x450
Weight	kg(lbs)			15.5 (34)	15.5 (34)	15.5 (34)	15.5 (34)
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
External static pressure	Pa			0 to 30	0 to 30	0 to 30	0 to 50
Drain pump	Standard						

Slim duct



Model No.	Indoor unit			ARXG07KLLAP	ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP
kW Class	kW			2.0	2.5	3.5	4.0
Power Source	Single-phase, ~230V, 50Hz						
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26
	Heating			28/26/25/24	28/26/25/24	29/28/27/24	32/30/28/25
Sound Power Level	Cooling	H	dB(A)	57	57	58	60
	Heating			57	57	58	60
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480
	Heating			550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480
Net Dimensions	mm			198x700x620	198x700x620	198x700x620	198x700x620
Weight	kg(lbs)			16 (35)	17 (37)	17 (37)	17 (37)
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
External static pressure	Pa			0 to 90	0 to 90	0 to 90	0 to 90
Drain pump	Standard						

MULTI SPLIT

2 - 8 Rooms Multi Indoor Units Specifications

Compact wall mounted



Model No.	Indoor unit			ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	ASYG14LUCA
kW Class		kW		2.0	2.5	3.5	4.0
Power Source				Single-phase, ~230V, 50Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	35/30/28/21	36/32/28/21	37/34/31/21	41/36/33/25
	Heating			35/30/28/21	36/32/28/21	37/34/31/21	41/36/34/27
Sound Power Level	Cooling	H	dB(A)	53	54	55	59
	Heating			53	54	55	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	570/520/470/330	600/550/470/330	660/600/530/330	710/640/570/390
	Heating			570/520/470/330	600/550/470/330	660/600/530/330	710/640/590/430
Net Dimensions			mm	282×870×185	282×870×185	282×870×185	282×870×185
Weight			kg(lbs)	9.5 (21)	9.5 (21)	9.5 (21)	9.5 (21)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

Wall mounted



Model No.	Indoor unit			ASYG18LFCA	ASYG24LFCC
kW Class		kW		5.0	7.0
Power Source				Single-phase, ~230V, 50Hz	
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	43/37/33/26	49/42/37/33
	Heating			42/37/33/25	48/42/37/33
Sound Power Level	Cooling	H	dB(A)	58	64
	Heating			58	64
Airflow Rate	Cooling	H/M/L/Q	m³/h	900/740/620/550	1,120/900/740/620
	Heating			900/740/620/550	1,100/900/740/620
Net Dimensions			mm	320×998×238	320×998×238
Weight			kg(lbs)	14 (30.8)	14 (30.8)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/12.70	6.35/15.88

Compact wall mounted



Model No.	Indoor unit			ASYG07LMCE	ASYG09LMCE	ASYG12LMCE	ASYG14LMCE
kW Class		kW		2.0	2.5	3.5	4.0
Power Source				Single-phase, ~230V, 50Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25
	Heating			36/32/29/22	37/33/29/22	40/36/31/22	42/38/35/27
Sound Power Level	Cooling	H	dB(A)	51	52	54	56
	Heating			51	52	55	57
Airflow Rate	Cooling	H/M/L/Q	m³/h	560/500/430/310	600/520/430/310	660/560/450/310	730/600/530/360
	Heating			560/500/430/330	600/520/430/330	660/560/470/330	730/615/560/375
Net Dimensions			mm	270×870×204	270×870×204	270×870×204	270×870×204
Weight			kg(lbs)	8.5 (18.7)	8.5 (18.7)	8.5 (18.7)	8.5 (18.7)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70

Floor




Model No.	Indoor unit			AGYG09LVCA	AGYG12LVCA	AGYG14LVCA
kW Class		kW		2.5	3.5	4.0
Power Source				Single-phase, ~230V, 50Hz		
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	39/34/28/22	42/36/30/22	44/38/31/22
	Heating			39/35/30/22	42/38/32/22	44/39/33/22
Sound Power Level	Cooling	H	dB(A)	52	55	56
	Heating			52	55	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	530/440/360/270	600/490/380/270	650/520/400/270
	Heating			530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions			mm	600×740×200	600×740×200	600×740×200
Weight			kg(lbs)	14 (30.7)	14 (30.7)	14 (30.7)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/12.70

Floor ceiling


Model No.	Indoor unit			ABYG14LVTA	ABYG18LVTB
kW Class		kW		4.0	5.0
Power Source	Single-phase, ~230V, 50Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
	Heating			36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
Sound Power Level	Cooling	H	dB(A)	51	55
	Heating			51	55
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	640/590/540/480	780/700/560/500
	Heating			640/590/540/480	780/700/560/500
Net Dimensions				199×990×655	199×990×655
Weight				27 (60)	27 (60)
Connection Pipe Diameter	Liquid/Gas	mm		6.35/12.70	6.35/12.70

Compact cassette


Model No.	Indoor unit			AUYG07LVLA	AUYG09LVLA	AUYG12LVLB	AUYG14LVLB	AUYG18LVLB
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source	Single-phase, ~230V, 50Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating			34/32/29/27	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Sound Power Level	Cooling	H	dB(A)	46	46	49	52	54
	Heating			47	47	49	52	56
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Net Dimensions				245×570×570	245×570×570	245×570×570	245×570×570	245×570×570
Weight				15(33.1)	15 (33.1)	15 (33.1)	15 (33.1)	15 (33.1)
Panel	UTG-UFYD-W							
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70

Mini duct


Model No.	Indoor unit			ARYG07LSLAP	ARYG09LSLAP	ARYG12LSLAP	ARYG14LSLAP	ARYG18LSLAP
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source	Single-phase, ~230V, 50Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
	Heating			29/26/24/23	29/26/24/23	31/27/25/23	35/30/27/23	33/29/26/23
Sound Power Level	Cooling	H	dB(A)	52	54	55	60	58
	Heating			53	56	57	62	59
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
	Heating			550/440/390/360	600/450/400/360	650/490/430/360	800/640/530/360	940/750/540/480
Net Dimensions				198×700×450	198×700×450	198×700×450	198×700×450	198×900×450
Weight				15.5 (34.1)				18.5 (40.7)
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52			6.35/12.70	
External static pressure				0 to 30			0 to 50	
Drain pump	Standard							

Slim duct


Model No.	Indoor unit			ARYG07LLTA	ARYG09LLTA	ARYG12LLTB	ARYG14LLTB	ARYG18LLTB
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source	Single-phase, ~230V, 50Hz							
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26	32/31/30/29
	Heating			28/26/25/24	28/26/25/24	29/28/27/24	33/30/28/25	33/32/31/29
Sound Power Level	Cooling	H	dB(A)	57	57	58	60	58
	Heating			57	57	58	61	59
Airflow Rate	Cooling	H/M/L/Q	m ³ /h	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
	Heating			550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
Net Dimensions				198×700×620	198×700×620	198×700×620	198×700×620	198×900×620
Weight				17 (37.5)	19 (41.8)	19 (41.8)	19 (41.8)	23 (50.6)
Connection Pipe Diameter	Liquid/Gas	mm		6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.70
External static pressure				0 to 90				
Drain pump	Standard							